

Economy Standard Twist Wheels - Extra Heavy-Duty

A value-priced option for automatic and semi-automatic equipment. Ideal for gear deburring.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Ref. Code	Item No. Steel
14"	.014	2"◆	90	3/4"	1/2"	5/8"	5,000	EKHD-1490	09020
	.014	1-1/4"★							09029
	.020	2"◆							09040
	.020	1-1/4"★							09049
15"	.0118	2"◆	90	3/4"	2"	5/8"	5,000	EKHD-1590	09050
	.0118	1-1/4"★							09059
	.014	2"◆							09060
	.014	1-1/4"★							09069
	.020	2"◆							09080
	.020	1-1/4"★							09089

★ 5/16" x 5/32" Double Keyway ◆ 1/2" x 1/4" Double Keyway

Cleaning a crack on an airport runway prior to filling.



09020

Cable Twist Wheels -

Maximum impact for extremely severe applications.



Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. AH Avail.	Thickness at Face Plates	Max. RPM	Ref. Code	Item No.	
										Steel	Stainless
4"	.020	1/2"-3/8" M10 x 1.25 M10 x 1.50 M14 x 2.0 1/2"-13 UNC 5/8"-11 UNC	24	1/4"	7/8"	1/2"	7/16"	20,000	CT-4 CTA-4	08534	—
										13261	—
										13262	13272
										13263	—
										13265	—
										13266 ■	13276
6"	.023	5/8"-1/2"	24	3/8"	1-3/8"	1-1/4"	9/16"	9,000	CT-6	08565	08695
8"	.023	5/8"	38	1/2"	1-5/8"	2"	1/2"	6,000	CT-8	08615	—
10"	.023	3/4" 1-1/4"★ with keyway	52	1/2"	1-3/4"	2-1/2"	3/4"	4,500	CT-10	08878	—
										08879	—
12"	.023	1-1/4"★ with keyway	52	7/16"	2-3/4"	3"	3/4"	3,600	CT-12	09379	—

★ 5/16" x 5/32" Double Keyway

■ Available in Display Packaging. Add "P" to end of Item No. when placing order.



13266

Cable Twist Wheels - Wide Face

Ideal for external pipe cleaning. For automatic and semi-automatic equipment.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Max. AH Avail.	Thickness at Face Plates	Max. RPM	Ref. Code	Item No. Steel
10"	.023	2"	208	1-3/4"	1-3/4"	2"	1-7/8"	4,500	WCT-10-4	94008




94008

Cable Twist Wheels - Joint/Crack Cleaning Brushes

For brushing joints or cleaning cracks in concrete and asphalt; preparing expansion joints for filling and sealing. Used on walk-behind machines.

Dia.	Wire Size	Arbor Hole	No. of Knots	Face Width	Trim Length	Thickness at Face Plates	Max. RPM	Ref. Code	Item No. Steel
10"	.035	1" with two drive holes*	38	3/8"	2-5/8"	1/2"	5,000	QCT-10	94199
12"	.035	1" with two drive holes*	38	3/8"	3-5/8"	1/2"	5,000	QCTL-12	94224
12"	.035	1" with two drive holes*	52	3/8"	2-3/4"	3/4"	5,000	QCT-12	94026

* Drive holes are 3/8" diameter.



94224

Adapter - For Joint/Crack Cleaning Brushes

For Brush Arbor Hole Size	Adapted Arbor Hole Size	Item No.
1"	20mm	04455



04455

Dualife® Knot Wire Wheels