

# Nylox® FME Area Product Solutions




Cleaning internal threads inside a valve.



86148



86159



86171



44144



95016

## End Brush - Crimped Ceramic Filament - 1/4" Stem For spot-facing or cleaning in tight areas.



Diameter	Filment Dia./Grit Size	Trim Length	Max. RPM	Standard Pack	Item Number
1"	.055/80	3/4"	4,800	10	86148

## Controlled Flare End Brush - Crimped Ceramic Filament - 1/4" Stem For cleaning corners and tight areas.



Diameter	Filment Dia./Grit Size	Trim Length	Max. RPM	Standard Pack	Item Number
1"	.035/80	1-1/8"	4,800	10	86159

## Conflex Brushes - Crimped Ceramic Filament - 1/4" Stem For O.D. and I.D. cleaning in confined areas.



Diameter	Filment Dia./Grit Size	Face Width	Trim Length	Max. RPM	Standard Pack	Item No.
3"	.043/120	1"	15/16"	4,800	10	86171
3"	.055/80	1"	15/16"	4,800	10	86172



Nylon abrasive filament brushes require a lower operating RPM than most other power tool accessories and they cannot be used effectively on standard grinders.



## Model 60006 Die Grinder

### Features:

- Double insulation
- 4,800 RPM
- Deadman switch
- Spindle lock
- Side handle included
- 7.5 Amp
- 1/4" Collet
- Extended spindle for working in confined areas

## Hand Scratch Brushes - Crimped Ceramic Filament - For general purpose, light-duty cleaning.

Overall Length	Block Type	Brush Part	Grit Size	Trim Length	Standard Pack	Item No.
10"	Wood	5"	80	3/4"	12	44144
8-3/4"	Wood	2 x 9 Rows	120	5/8"	36	95016

**DID YOU KNOW?**

Weiler's Nylox and Burr-Rx brushes are used by all three of the major jet engine manufacturers to deburr critical component parts.